

# Regulated Rewriting – The Hierarchy

Jiří Techet    Tomáš Masopust    Alexander Meduna

Department of Information Systems  
Faculty of Information Technology  
Brno University of Technology  
Božetěchova 2, Brno 61266, Czech Republic

Modern Formal Language Theory, 2007

# Hierarchy of Language Families – Description

## Notation

*ac* appearance checking

$\varepsilon$  with erasing productions

*M* matrix grammars

*P* programmed grammars

*RC* random context grammars

*PER* permitting grammars


*FOR* forbidding grammars

0, 1, 2 type-0, type-1, type-2 grammars, respectively

## Example

$\mathcal{L}(RC, \varepsilon, ac)$  – the family of languages generated by **random context grammars** with **erasing productions** in **appearance checking** mode

# Regulated Rewriting – The Hierarchy



# Proof of $\mathcal{L}(M) = \mathcal{L}(P)$

## Theorem

$$\mathcal{L}(M) = \mathcal{L}(P).$$

## Proof–Basic Idea

- 1  $\mathcal{L}(M) \subseteq \mathcal{L}(P)$ : Transform any matrix grammar to an equivalent programmed grammar
- 2  $\mathcal{L}(P) \subseteq \mathcal{L}(M)$ : Transform any programmed grammar to an equivalent matrix grammar
- 3  $\mathcal{L}(M) = \mathcal{L}(P)$

# Proof of $\mathcal{L}(M) \subseteq \mathcal{L}(P)$ I

Let

$$H = (G, M)$$

be a matrix grammar, where

- $G = (N, T, P, S)$  is a context-free grammar
- $M$  is a finite language over  $P$

Express  $M$  as

$$M = \{m_1, \dots, m_r\}$$

for some  $r \geq 1$  and

$$m_i = p_{i_1} \dots p_{i_{k_i}}$$

with  $k_i = |m_i|$ . Set

$$N' = \{A' : A \in N\}$$

Define the homomorphism  $h$  from  $(T \cup N)^*$  to  $(T \cup N')^*$  as

- $h(a) = a$  for every  $a \in T$
- $h(A) = A'$  for every  $A \in N$

# Proof of $\mathcal{L}(M) \subseteq \mathcal{L}(P)$ II

- 1 For every  $p_{i_j} : A_{i_j} \rightarrow x_{i_j}$  such that  $\text{alph}(x_{i_j}) \cap N \neq \emptyset$  (some nonterminals occur in  $x_{i_j}$ ) and  $j < |m_i|$  (not the last production in  $m_i$ ), introduce this programmed production:

$$(\langle i, j \rangle : A_{i_j} \rightarrow x_{i_j}, \{\langle i, j+1 \rangle\})$$

- 2 For every  $p_{i_j} : A_{i_j} \rightarrow x_{i_j}$  such that  $\text{alph}(x_{i_j}) \cap N = \emptyset$  (no nonterminal occurs in  $x_{i_j}$ ) and  $j < |m_i|$  (not the last production in  $m_i$ ), introduce
- a  $(\langle i, j \rangle : A_{i_j} \rightarrow h(A_{i_j}), \{\langle i, j, 1 \rangle, \dots, \langle i, j, m \rangle\})$
  - b  $(\langle i, j, q \rangle : A_q \rightarrow A_q, \{\langle i, j \rangle'\})$  for  $q = 1, \dots, m$  (make sure there is a nonterminal)
  - c  $(\langle i, j \rangle' : h(A_{i_j}) \rightarrow x_{i_j}, \{\langle i, j+1 \rangle\})$
- provided that  $N = \{A_1, \dots, A_m\}$
- 3 For every  $p_{i_{k_i}} : A_{i_{k_i}} \rightarrow x_{i_{k_i}}$  (simulate the last production of  $m_i$  and start simulating a new matrix), introduce

$$(\langle i, k_i \rangle : A_{i_{k_i}} \rightarrow x_{i_{k_i}}, \{\langle 1, 1 \rangle, \dots, \langle r, 1 \rangle\})$$

## Proof of $\mathcal{L}(M) \subseteq \mathcal{L}(P)$ III

Let  $P'$  consist of all rules constructed above and

$$(\$ : \bar{S} \rightarrow S, \{\langle 1, 1 \rangle, \dots, \langle r, 1 \rangle\})$$

Define the programmed grammar

$$G' = (N \cup N' \cup \{\bar{S}\}, T, P', \bar{S})$$

Observe that

$$L(H) = L(G')$$



# Proof of $\mathcal{L}(P) \subseteq \mathcal{L}(M)$ I

Let

$$H = (G, R)$$

be a programmed grammar. Consider the simplified description of  $H$  which uses productions of the form

$$(p : A \rightarrow x, R(p))$$

- 1 If  $(p : A \rightarrow x, Q), (r : B \rightarrow y, R) \in P$  and  $r \in Q$ , then introduce the matrix

$$(\langle A \rightarrow x \rangle \rightarrow A, A \rightarrow x, B \rightarrow \langle B \rightarrow y \rangle)$$

(simulation will continue)

- 2 If  $(p : A \rightarrow x, Q) \in P$ , then introduce

$$(\langle A \rightarrow x \rangle \rightarrow A, A \rightarrow x)$$

(simulation ends)



## Proof of $\mathcal{L}(P) \subseteq \mathcal{L}(M)$ II

3 If  $(p : S \rightarrow x, Q) \in P$ , introduce

$$(S' \rightarrow \langle S \rightarrow x \rangle)$$

(simulation starts)

Set

$$\begin{aligned} N' &= N \\ &\cup \{ \langle A \rightarrow x \rangle : A \rightarrow x \in P \} \\ &\cup \{ S' \} \end{aligned}$$

Define the matrix grammar

$$G' = (N', T, P', S')$$

where  $P'$  consists of all the above matrices. Observe that

$$L(H) = L(G')$$





S. Abraham.

Some questions of phrase-structure grammars.

*Computational Linguistics*, 4:61–70, 1965.



J. Dassow and Gh. Păun.

*Regulated Rewriting in Formal Language Theory*.

Akademie-Verlag, Berlin, 1989.



H. Fernau and H. Bordihn.

Accepting grammars and systems via context condition grammars.


*Journal of Automata, Languages and Combinatorics*, 1(2):97–112, 1996.




D. J. Rosenkrantz.

Programmed grammars and classes of formal languages.

*Journal of the ACM*, 16:107–131, 1969.

 G. Rozenberg and A. Salomaa.  
*Handbook of Formal Languages*, volume 1–3.  
Springer, Berlin, 1997.

 A. P. J. van der Walt.  
Random context grammars.  
In *Proceedings of Symposium on Formal Languages*, 1970.