

# Parallel Communicating Grammar Systems

Jiří Techet    Tomáš Masopust    Alexander Meduna

Department of Information Systems  
Faculty of Information Technology  
Brno University of Technology  
Božetěchova 2, Brno 61266, Czech Republic

Modern Formal Language Theory, 2007

## PC Grammar System

A **parallel communicating (PC) grammar system** of degree  $n$ ,  $n \geq 1$ , is a construct

$$\Gamma = (N, K, T, (S_1, P_1), \dots, (S_n, P_n))$$

where

$K$  is a finite set of **query symbols**,  $K = \{Q_1, \dots, Q_n\}$

$P_i$  is a finite set of productions of the form

$$A \rightarrow x$$

with  $A \in N$  and  $x \in (N \cup T \cup K)^*$ , for all  $i = 1, \dots, n$

$S_i$  is the start symbol of the  $i$ th component,  $S_i \in N$  for all  $i = 1, \dots, n$

$N, T$  are defined as usual,  $N, K, T$  are pairwise disjoint

## Two Kinds of Derivation Steps

- generating
- communicating

## g-Step

If

- either  $x_i \Rightarrow y_i$  in  $G_i = (N \cup K, T, P_i, S_i)$ ,
- or  $x_i = y_i \in T^*$

for all  $1 \leq i \leq n$ , then

$$(x_1, \dots, x_n) \xRightarrow{g} (y_1, \dots, y_n)$$

## c-Step

- set  $z_i = x_i$  for all  $i = 1, \dots, n$

For each  $i = 1, \dots, n$ , if

$$\text{alph}(x_i) \cap K \neq \emptyset$$

and for each  $Q_j$  in  $x_i$ ,

$$\text{alph}(x_j) \cap K = \emptyset,$$

then for each  $Q_j$  in  $x_i$

- 1 set  $z_j = S_j$ ,
- 2 replace  $Q_j$  with  $x_j$  in  $x_i$ ,
- 3 set  $z_i$  to the string resulting from (2)

Perform

$$(x_1, \dots, x_n) \xrightarrow{c} (y_1, \dots, y_n)$$

with  $y_i = z_i$ , for all  $i = 1, \dots, n$

## Direct Derivation

If either

$$(x_1, \dots, x_n) \xrightarrow{g} (y_1, \dots, y_n)$$

or

$$(x_1, \dots, x_n) \xrightarrow{c} (y_1, \dots, y_n)$$

then

$$(x_1, \dots, x_n) \Rightarrow (y_1, \dots, y_n)$$

## Generated Language

$$L(\Gamma) = \{x \in T^* : (S_1, S_2, \dots, S_n) \Rightarrow^* (x, \alpha_2, \dots, \alpha_n), \\ \alpha_i \in (N \cup T \cup K)^*, \text{ for all } i = 2, \dots, n\}$$

# Centralized PC Grammar Systems

- only  $P_1$  can produce query symbols

## Centralized PC Grammar System

Let

$$\Gamma = (N, K, T, (S_1, P_1), \dots, (S_n, P_n))$$

be a PC grammar system.  $\Gamma$  is **centralized** if for all  $A \rightarrow x \in P_i$ , where  $i = 2, \dots, n$ ,

$$\text{alph}(x) \cap K = \emptyset$$

# Returning and Non-Returning PC Grammar Systems

## Returning PC Grammar System

After communicating, each component that has sent its string to another component **returns** to its axiom.

- generated language denoted by  $L_r(\Gamma)$

## Non-Returning PC Grammar System

After communicating, each component that has sent its string to another component **continues** to process the current string. That is, remove (1) in the basic definition.

- generated language denoted by  $L_{nr}(\Gamma)$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, \textcolor{red}{S}_1 \rightarrow \textcolor{red}{a}S'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{\textcolor{red}{S}_2 \rightarrow \textcolor{red}{b}S_2\}$$

$$P_3 = \{\textcolor{red}{S}_3 \rightarrow \textcolor{red}{c}S_3\}$$

$$(S_1, S_2, S_3)$$



## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{S_2 \rightarrow bS_2\}$$

$$P_3 = \{S_3 \rightarrow cS_3\}$$

$$(S_1, S_2, S_3) \Rightarrow (aS'_1, bS_2, cS_3)$$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{S_2 \rightarrow bS_2\}$$

$$P_3 = \{S_3 \rightarrow cS_3\}$$

$$(S_1, S_2, S_3) \Rightarrow (aS'_1, bS_2, cS_3) \Rightarrow^* (a^n S'_1, b^n S_2, c^n S_3)$$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{S_2 \rightarrow bS_2\}$$

$$P_3 = \{S_3 \rightarrow cS_3\}$$

$$(S_1, S_2, S_3) \Rightarrow (aS'_1, bS_2, cS_3) \Rightarrow^* (a^n S'_1, b^n S_2, c^n S_3) \\ \Rightarrow (a^{n+3} \textcolor{red}{Q}_2, b^{n+1} S_2, c^{n+1} S_3)$$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{S_2 \rightarrow bS_2\}$$

$$P_3 = \{S_3 \rightarrow cS_3\}$$

$$(S_1, S_2, S_3) \Rightarrow (aS'_1, bS_2, cS_3) \Rightarrow^* (a^n S'_1, b^n S_2, c^n S_3) \\ \Rightarrow (a^{n+3} Q_2, b^{n+1} S_2, c^{n+1} S_3) \Rightarrow (a^{n+3} b^{n+1} S_2, S_2, c^{n+1} S_3)$$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{S_2 \rightarrow bS_2\}$$

$$P_3 = \{S_3 \rightarrow cS_3\}$$

$$\begin{aligned} (S_1, S_2, S_3) &\Rightarrow (aS'_1, bS_2, cS_3) \Rightarrow^* (a^n S'_1, b^n S_2, c^n S_3) \\ &\Rightarrow (a^{n+3} Q_2, b^{n+1} S_2, c^{n+1} S_3) \Rightarrow (a^{n+3} b^{n+1} S_2, S_2, c^{n+1} S_3) \\ &\Rightarrow (a^{n+3} b^{n+3} Q_3, bS_2, c^{n+2} S_3) \end{aligned}$$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, \textcolor{red}{S}_3 \rightarrow \textcolor{red}{c}\}$$

$$P_2 = \{\textcolor{red}{S}_2 \rightarrow \textcolor{red}{bS}_2\}$$

$$P_3 = \{\textcolor{red}{S}_3 \rightarrow \textcolor{red}{cS}_3\}$$

$$\begin{aligned} (S_1, S_2, S_3) &\Rightarrow (aS'_1, bS_2, cS_3) \Rightarrow^* (a^n S'_1, b^n S_2, c^n S_3) \\ &\Rightarrow (a^{n+3} Q_2, b^{n+1} S_2, c^{n+1} S_3) \Rightarrow (a^{n+3} b^{n+1} S_2, S_2, c^{n+1} S_3) \\ &\Rightarrow (a^{n+3} b^{n+3} Q_3, bS_2, c^{n+2} S_3) \Rightarrow (a^{n+3} b^{n+3} \textcolor{red}{c}^{n+2} \textcolor{red}{S}_3, bS_2, \textcolor{red}{S}_3) \end{aligned}$$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{S_2 \rightarrow bS_2\}$$

$$P_3 = \{S_3 \rightarrow cS_3\}$$

$$\begin{aligned} (S_1, S_2, S_3) &\Rightarrow (aS'_1, bS_2, cS_3) \Rightarrow^* (a^n S'_1, b^n S_2, c^n S_3) \\ &\Rightarrow (a^{n+3} Q_2, b^{n+1} S_2, c^{n+1} S_3) \Rightarrow (a^{n+3} b^{n+1} S_2, S_2, c^{n+1} S_3) \\ &\Rightarrow (a^{n+3} b^{n+3} Q_3, bS_2, c^{n+2} S_3) \Rightarrow (a^{n+3} b^{n+3} c^{n+2} S_3, bS_2, S_3) \\ &\Rightarrow (a^{n+3} b^{n+3} c^{n+3}, bbS_2, cS_3) \end{aligned}$$

## Example

$$\Gamma = (\{S_1, S'_1, S_2, S_3\}, K, \{a, b\}, (S_1, P_1), (S_2, P_2), (S_3, P_3))$$

where

$$P_1 = \{S_1 \rightarrow abc, S_1 \rightarrow a^2b^2c^2, S_1 \rightarrow aS'_1, S_1 \rightarrow a^3Q_2, \\ S'_1 \rightarrow aS'_1, S'_1 \rightarrow a^3Q_2, S_2 \rightarrow b^2Q_3, S_3 \rightarrow c\}$$

$$P_2 = \{S_2 \rightarrow bS_2\}$$

$$P_3 = \{S_3 \rightarrow cS_3\}$$

$$\begin{aligned} (S_1, S_2, S_3) &\Rightarrow (aS'_1, bS_2, cS_3) \Rightarrow^* (a^n S'_1, b^n S_2, c^n S_3) \\ &\Rightarrow (a^{n+3} Q_2, b^{n+1} S_2, c^{n+1} S_3) \Rightarrow (a^{n+3} b^{n+1} S_2, S_2, c^{n+1} S_3) \\ &\Rightarrow (a^{n+3} b^{n+3} Q_3, bS_2, c^{n+2} S_3) \Rightarrow (a^{n+3} b^{n+3} c^{n+2} S_3, bS_2, S_3) \\ &\Rightarrow (a^{n+3} b^{n+3} c^{n+3}, bbS_2, cS_3) \end{aligned}$$

$$L_r(\Gamma) = L_{nr}(\Gamma) = \{a^n b^n c^n : n \geq 1\}$$



# Denotation of PC Language Families

## Denotation of PC Language Families

$XPC_nY$

$X$

$N$  – non-returning mode

$C$  – centralized PC grammar systems

$n$  number of components (by analogy with CD grammar systems)

$Y$  specification of the type of productions ( $REG$ ,  $LIN$ ,  $CF$ )

## Example

$CPC_2REG$ ,  $NPC_2LIN$ ,  $NCPC_\infty$

## Theorem

- $PC_nREG - \mathcal{L}(LIN) \neq \emptyset$ , for  $n \geq 2$
- $PC_nREG - \mathcal{L}(CF) \neq \emptyset$ , for  $n \geq 3$
- $PC_nLIN - \mathcal{L}(CF) \neq \emptyset$ , for  $n \geq 2$

## Theorem

$$\mathcal{L}(LIN) - CPC_{\infty}REG \neq \emptyset$$

## Theorem

$PC_n REG \subset PC_{n+1} REG$ , for  $n \geq 1$


## Theorem


$CPC_n REG \subset CPC_n LIN \subset CPC_n CF$ , for  $n \geq 1$


## Theorem

- $NPC_\infty CF \subseteq PC_\infty CF$
- $\mathcal{L}(M) \subset PC_\infty CF$
- $\mathcal{L}(LIN) \subset PC_\infty REG$

# PC Grammar Systems – The Hierarchy



 Grammar systems.  
<http://www.sztaki.hu/mms/bib.html>.

 Gh. Păun and L. Sântean.  
Parallel communicating grammar systems: the regular case.  
*Annals Universitatis Bucharest, Mathematics-Informatics Series*,  
38:55–63, 1989.