

# Scattered Context Generators of Sentences With Their Parses

Jiří Techet    Tomáš Masopust    Alexander Meduna

Department of Information Systems  
Faculty of Information Technology  
Brno University of Technology  
Božetěchova 2, Brno 61266, Czech Republic

Modern Formal Language Theory, 2007

# Scattered Context Grammar (SC grammar)

**Scattered context grammar**  $G = (V, T, P, S)$

$V$  is a finite alphabet

$T$  is a set of terminals,  $T \subset V$

$S$  is a starting symbol,  $S \in (V - T)$

$P$  is a finite set of productions of the form  $(A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n)$ ;  
 $A_1, \dots, A_n \in (V - T)$ ;  $x_1, \dots, x_n \in V^*$

**Propagating scattered context grammar (PSC grammar)**

- special case of SC grammar

- every  $(A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n)$  satisfies  $x_1, \dots, x_n \in V^+$

# SC Grammars – Generated Language

## Derivation step

If

$$\blacksquare (A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n) \in P$$

$$\blacksquare u = u_1 A_1 \dots u_n A_n u_{n+1}$$

$$\blacksquare v = u_1 x_1 \dots u_n x_n u_{n+1}$$

then  $u \Rightarrow v [(A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n)]$

## Generated language

$$L(G) = \{x : x \in T^*, S \Rightarrow^* x\}$$

## Generative power

$$\blacksquare \mathcal{L}(SCG) = \mathcal{L}(RE)$$

$$\blacksquare \mathcal{L}(CF) \subset \mathcal{L}(PSCG) \subseteq \mathcal{L}(CS)$$

# SC Grammars – Example

## Example

$$G_1 = (V_1, T_1, P_1, S),$$

where

$$V_1 = \{a, b, c, A, B, C, S\}, T_1 = \{a, b, c\},$$

$$P_1 = \{(S) \rightarrow (ABC), \\ (A, B, C) \rightarrow (aA, bB, cC), \\ (A, B, C) \rightarrow (\varepsilon, \varepsilon, \varepsilon)\}$$

$$S \Rightarrow ABC \Rightarrow aAbBcC \Rightarrow aaAbbBccC \Rightarrow aaaAbbbbBcccC \Rightarrow aaabbbcccc \\ L(G_1) = \{a^n b^n c^n : n \geq 0\}$$

$G_1$  is a SC grammar

$G_1$  is not a PSC grammar

# Production Labels I

- for every grammar,  $G$ , there is a set of production labels
- we denote them  $lab(G)$
- every  $p \in lab(G)$  uniquely identifies one production
- we write  $p : (A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n)$

## Example

$$G_2 = (\{S, A, B, C, a, b, c\}, \{a, b, c\}, P_2, S)$$

$$lab(G_2) = \{1, 2, 3\}$$

$$\begin{aligned} P_2 = \{ & 1 : (S) \rightarrow (ABC), \\ & 2 : (A, B, C) \rightarrow (aA, bB, cC), \\ & 3 : (A, B, C) \rightarrow (\epsilon, \epsilon, \epsilon) \} \end{aligned}$$

$$L(G_2) = \{a^n b^n c^n : n \geq 0\}$$

# Production Labels II

- to express that  $x \Rightarrow y$  by  $p : (A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n)$ , we write  $x \Rightarrow y [p]$

## Example

$S \Rightarrow ABC [1] \Rightarrow aAbBcC [2] \Rightarrow aaAbbBccC [2] \Rightarrow aabbcc [3]$  in  $G_2$

- to express that  $x \Rightarrow^* y$  by productions labeled with  $p_1, \dots, p_n$ , we write  $x \Rightarrow^* y [p_1 \dots p_n]$
- $p_1 \dots p_n \in lab(G)^*$

## Example

$S \Rightarrow^* aabbcc [1223]$  in  $G_2$

$1223 \in lab(G_2)^*$

# Proper Generator of its Sentences with Their Parses I

## Parse

If  $S \Rightarrow^* x [\rho]$ ,  $x \in T^*$ ,  $\rho \in \text{lab}(G)^*$ , then  $x$  is a sentence generated by  $G$  according to parse  $\rho$

## Example

$aabbcc$  is a sentence generated according to parse 1223 in  $G_2$

## Proper generator of its sentences with their parses

- $G$  is a proper generator of its sentences with their parses if
$$L(G) = \{x : x = y\rho, y \in (T - \text{lab}(G))^*, \rho \in \text{lab}(G)^*, S \Rightarrow^* x [\rho]\}$$

# Proper Generator of its Sentences with Their Parses

## II

### Example

$$G_3 = (\{S, A, B, C, a, b, c, 1, 2, 3, \$\}, \{a, b, c, 1, 2, 3\}, P_3, S) \\ lab(G_3) = \{1, 2, 3\}$$

$$P_3 = \{1 : (S) \rightarrow (ABC1\$) \\ 2 : (A, B, C, \$) \rightarrow (aA, bB, cC, 2\$) \\ 3 : (A, B, C, \$) \rightarrow (\epsilon, \epsilon, \epsilon, 3)\}$$

$$S \Rightarrow ABC1\$ [1] \Rightarrow aAbBcC12\$ [2] \Rightarrow aaAbbBccC122\$ [2] \Rightarrow \\ aabbcc1223 [3]$$

$$S \Rightarrow^* aabbcc1223 [1223]$$

$$L(G_3) = \{a^n b^n c^n \rho : n \geq 0, S \Rightarrow^* a^n b^n c^n \rho [\rho], \rho = 12^n 3\}$$

$G_3$  is a proper generator of its sentences with their parses



# Theorem 1

- let  $G = (V, T, P, S)$  be a proper generator of its sentences with their parses
- we define the weak identity  $\pi$  from  $V^*$  to  $(V - lab(G))^*$  as
  - $\pi(a) = a$  for every  $a \in (V - lab(G))$
  - $\pi(p) = \epsilon$  for every  $p \in lab(G)$

## Example

$\pi(aabbcc1223) = aabbcc$  in  $G_3$

## Theorem

*For every recursively enumerable language,  $L$ , there exists a PSC grammar,  $G$ , such that  $G$  is a proper generator of its sentences with their parses and  $L = \pi(L(G))$ .*

# Leftmost derivation step in SC grammars

## Derivation step in SC grammars

If

$$(A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n) \in P,$$

$$u = u_1 A_1 \dots u_n A_n u_{n+1},$$

$$v = u_1 x_1 \dots u_n x_n u_{n+1},$$

then  $u \Rightarrow v [(A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n)]$

■  $\text{alph}(w)$  denotes the set of all symbols occurring in  $w$

## Example

$$\text{alph}(\text{bacaab}) = \{a, b, c\}$$

## Leftmost derivation step in SC grammars

every  $A_i \notin \text{alph}(u_i)$  for all  $1 \leq i \leq n$

# Language Generated in a Leftmost Way

## Language generated in a leftmost way

$$L(G) = \{x : x \in T^*, S \Rightarrow^* x\}$$

- and every step in every generation of  $x \in T^*$  is leftmost

## Proper leftmost generator of its sentences with their parses

$$L(G) = \{x : x = y\rho, y \in (T - \text{lab}(G))^*, \rho \in \text{lab}(G)^*, S \Rightarrow^* x[\rho]\}$$

- and  $G$  generates  $L(G)$  in a leftmost way

# Language Generated in a Leftmost Way – Example

## Example

$$G_4 = (\{S, A, B, C, a, b, c, 1, 2, 3, 4, \$\}, P_4, S, \{a, b, c, 1, 2, 3, 4\})$$

$$lab(G_4) = \{1, 2, 3, 4\}$$

$$\begin{aligned} P_4 = \{ & 1 : (S) \rightarrow (ABC1\$), \\ & 2 : (A, B, C, \$) \rightarrow (AA, BB, CC, 2\$), \\ & 3 : (A, B, C, \$) \rightarrow (a, b, c, 3\$), \\ & 4 : (A, B, C, \$) \rightarrow (\epsilon, \epsilon, \epsilon, 4)\} \end{aligned}$$

$$\begin{aligned} S \Rightarrow ABC1\$ [1] \Rightarrow AABBBCC12\$ [2] \Rightarrow AabBCc123\$ [3] \Rightarrow \\ AAabBBCCc1232\$ [2] \Rightarrow aAabBbcCc12323\$ [3] \Rightarrow \\ aabbcc123234\$ [4] \end{aligned}$$

$$S \Rightarrow^* aabbcc123234 [123234]$$

$$L(G_4) = \{a^n b^n c^n \rho : n \geq 0, S \Rightarrow^* a^n b^n c^n \rho [\rho]\}$$

$G_4$  is a proper generator of its sentences with their parses

$G_4$  is not a proper leftmost generator of its sentences with their parses

# Theorem 2

- let  $G = (V, T, P, S)$  be a proper generator of its sentences with their parses
- we define the weak identity  $\pi$  from  $V^*$  to  $(V - lab(G))^*$  as
  - $\pi(a) = a$  for every  $a \in (V - lab(G))$
  - $\pi(p) = \epsilon$  for every  $p \in lab(G)$

## Example

$\pi(aabbcc123234) = aabbcc$  in  $G_4$

## Theorem

*For every recursively enumerable language,  $L$ , there exists a PSC grammar,  $G$ , such that  $G$  contains no more than six nonterminals,  $G$  is a proper leftmost generator of its sentences with their parses and  $L = \pi(L(G))$ .*

# Queue Grammar

- we represent the recursively enumerable language by a queue grammar

**Queue Grammar**  $G = (V, T, W, F, s, P)$

**V** is a finite alphabet of symbols

**T** is a set of terminals,  $T \subset V$

**W** is a finite alphabet of states

**F** is a set of final states,  $F \subset W$

**s** is a starting string,  $s \in (V - T)(W - F)$

**P** is a finite set of productions of the form:  $(a, b, x, c)$

**a**  $\in V$

**b**  $\in (W - F)$

**x**  $\in V^*$

**c**  $\in W$

# Queue Grammar – Derivation Step

## Derivation Step

If  $u = arb$ ,  $v = rxc$ ,  $a \in V$ ,  $r, x \in V^*$ ,  $b, c \in W$ , and  $(a, b, x, c) \in P$ , then  $u \Rightarrow v [(a, b, x, c)]$ .

## Generated Language

$$L(G) = \{w : s \Rightarrow^* wf, w \in T^*, f \in F\}$$

## Generative Power

$$\mathcal{L}(QG) = \mathcal{L}(RE)$$

## Lemma

*For every QG there exists an equivalent QG which generates every string so that it first uses only productions rewriting symbols over  $(V - T)^*$ , and then only symbols over  $T^*$ .*

# Queue Grammar – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ 3 : (a, \bar{e}, a, \bar{e}), \\ 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

$$\begin{aligned} A\bar{e} &\Rightarrow bAa\bar{e} [1] \Rightarrow Aab\bar{e} [4] \Rightarrow abbAa\bar{e} [1] \Rightarrow bbAaa\bar{e} [3] \Rightarrow bAaab\bar{e} [4] \\ &\Rightarrow Aaabb\bar{e} [4] \Rightarrow aabb\bar{f} [2] \end{aligned}$$

$$L(G_5) = \{a^n b^n : n \geq 0\}$$



# Proof Sketch

## Basic idea

- 1** represent the recursively enumerable language by a QG
  - 2** initiate the derivation
  - 3** simulate QG by PSC grammar
    - 1** simulate generation of words from  $(V - T)^*$
    - 2** simulate generation of words from  $T^+$
  - 4** check if the simulation was correct
  - 5** complete the derivation
- 
- every production has to add its label to the sentential form to create the parse in the correct order
  - generated sentence has to precede this parse

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ 3 : (a, \bar{e}, a, \bar{e}), \\ 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	$A$
States	$\bar{e}$
Productions	

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ \quad 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ \quad 3 : (a, \bar{e}, a, \bar{e}), \\ \quad 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	$A$	$b$	$A$	$a$
States	$\bar{e}$	$\bar{e}$		
Productions	1			

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ \quad 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ \quad 3 : (a, \bar{e}, a, \bar{e}), \\ \quad 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b
States	$\bar{e}$	$\bar{e}$	$\bar{e}$		
Productions	1	4			

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ \quad 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ \quad 3 : (a, \bar{e}, a, \bar{e}), \\ \quad 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b	b	A	a
States	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$				
Productions	1	4	1					

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ \quad 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ \quad 3 : (a, \bar{e}, a, \bar{e}), \\ \quad 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b	b	A	a	a
States	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$				
Productions	1	4	1	3					

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ \quad 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ \quad 3 : (a, \bar{e}, a, \bar{e}), \\ \quad 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b	b	A	a	a	b
States	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$				
Productions	1	4	1	3	4					

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ \quad 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ \quad 3 : (a, \bar{e}, a, \bar{e}), \\ \quad 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b	b	A	a	a	b	b
States	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$				
Productions	1	4	1	3	4	4					



# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ \quad 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ \quad 3 : (a, \bar{e}, a, \bar{e}), \\ \quad 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b	b	A	a	a	b	b
States	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{f}$			
Productions	1	4	1	3	4	4	2				

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ 3 : (a, \bar{e}, a, \bar{e}), \\ 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b	b	A	a	a	b	b
States	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{f}$			
Productions	1	4	1	3	4	4	2				
Prod. (queue)	1,2	4	1,2	3	4	4	1,2				
Prod. (state)	1-4	1-4	1-4	1-3,4	1-4	1-4	1,2-4				
Simulated pr.	1	4	1	3	4	4	2				

# QG Simulation – Example

## Example

$$G_5 = (\{A, a, b\}, \{a, b\}, \{\bar{e}, \bar{f}\}, \{\bar{f}\}, A\bar{e}, P_5)$$

$$P_5 = \{ \begin{array}{l} 1 : (A, \bar{e}, bAa, \bar{e}), \\ 2 : (A, \bar{e}, \varepsilon, \bar{f}), \\ 3 : (a, \bar{e}, a, \bar{e}), \\ 4 : (b, \bar{e}, b, \bar{e}) \end{array} \}$$

Queue	A	b	A	a	b	b	A	a	a	b	b
States	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{e}$	$\bar{f}$			
Productions	1	4	1	3	4	4	2				
Prod. (queue)	1,2	4	1,2	3	4	4	1,2				
Prod. (state)	1-4	1-4	1-4	1-3,4	1-4	1-4	1,2-4				
Simulated pr.	1	4	1	3	4	4	2				

# Construction I

- $Q = (V, T, W, F, s, R), L(Q) = L$
- $\alpha$ : injection from  $lab(Q)$  to  $\{\bar{0}\}^*\{\bar{1}\}$
- $f(a) = \{\alpha(r) : r : (a, b, x, c) \in R\}$  for all  $a \in V$
- $g(b) = \{\alpha(r) : r : (a, b, x, c) \in R\}$  for all  $b \in W$

## Constructed PSC grammar

$$G = (\{S, A, B, \#, \bar{0}, \bar{1}\} \cup T \cup lab(G), T \cup lab(G), P, S)$$

- the construction of  $P$  and  $lab(G)$  is demonstrated on the following slides

# Construction II

## Step 1 (initialization)

For every  $\bar{a}_0 \in f(a_0)$ ,  $\bar{q}_0 \in g(q_0)$  such that  $s = a_0q_0$ , add

$$\lfloor 1\bar{a}_0\bar{q}_0 \rfloor : (S) \rightarrow (A\lfloor 1\bar{a}_0\bar{q}_0 \rfloor AA\bar{q}_0A\bar{a}_0AB)$$

## Step 2 (simulation of $Q$ 's productions generating words over $V-T$ )

For every  $r : (a, b, x, d) \in R$ ,  $x \in (V - T)^*$  and  $d \in (W - F)$ ,  $\bar{x} \in f(x)$ ,  $\bar{d} \in g(d)$ , add

$$\lfloor 2r\bar{x}\bar{d} \rfloor : (A, A, A, A, A, B) \rightarrow (A, \lfloor 2r\bar{x}\bar{d} \rfloor A, \alpha(r)A, \bar{d}A, \bar{x}A, B)$$

## Step 3 (separation of steps 2 and 4)

Add

$$\lfloor 3 \rfloor : (A, A, A, A, A, B) \rightarrow (A, \lfloor 3 \rfloor A, A, A, B, A)$$

# Construction III

## Step 4 (simulation of $Q$ 's productions generating words over $T$ )

For every  $r : (a, b, c, d) \in R$ ,  $c \in T$  and  $d \in (W - F)$ ,  $\bar{d} \in g(d)$ , add

$$\lfloor 4r\bar{d} \rfloor : (A, A, A, A, B, A) \rightarrow (cA, \lfloor 4r\bar{d} \rfloor A, \alpha(r)A, \bar{d}A, B, A)$$

## Step 5 (simulation of $Q$ 's final step)

For every  $r : (a, b, c, d) \in R$ ,  $c \in T$  and  $d \in F$ , add

$$\lfloor 5r \rfloor : (A, A, A, A, B, A) \rightarrow (c, \lfloor 5r \rfloor A, \alpha(r)A, A, B, AA)$$

# Construction IV

## Step 6 (simulation verification)

Add

$$[6] : (A, \bar{0}, A, \bar{0}, A, \bar{0}, B, A, A) \rightarrow ([6], A, \#, A, \#, A, B, A, A),$$

$$[7] : (A, \bar{1}, A, \bar{1}, A, \bar{1}, B, A, A) \rightarrow ([7], A, \#, A, \#, A, B, A, A)$$

## Step 7 (finishing the derivation)

Add

$$[8] : (A, A, A, B, A, A) \rightarrow ([8]B, \#, \#, \#, \#, \#),$$

$$[9] : (B, \#) \rightarrow ([9], B),$$

$$[10] : (B) \rightarrow ([10])$$

# Theorem 3

- $\rho((A_1, \dots, A_n) \rightarrow (x_1, \dots, x_n)) = n$
- $\rho_{\max}(G) = \rho(p)$ ,  $p \in P$ , such that  $\rho(p) \geq \rho(r)$  for all  $r \in P$

## Theorem

*For every recursively enumerable language,  $L$ , there exists a PSC grammar,  $G$ , such that  $G$  is a proper leftmost generator of its sentences preceded by their parses,  $G$  contains no more than six nonterminals,  $\rho_{\max}(G) = 4$ , and  $L = \pi(L(G))$ .*

## Theorem

*For every recursively enumerable language,  $L$ , there exists a PSC grammar,  $G$ , such that  $G$  is a proper leftmost generator of its sentences preceded by their parses,  $G$  contains no more than nine nonterminals,  $\rho_{\max}(G) = 2$ , and  $L = \pi(L(G))$ .*



# Conclusion

## We have proved that

- for every RE there is a PSC grammar which generates its sentences with their parses
- there are canonical versions of these generators
- the number of needed nonterminals can be reduced

## Future investigation

- which other grammars can be used as proper generators of their sentences with their parses?
  - grammar systems seem to be appropriate candidates
- is it possible to generate sentences together with other useful information (e.g. derivation trees)?